



Most Beams Available in Lengths of: 20', 25', 30', 35', 40', 45', 50', 55', 60'

| <b>D Depth of Channel &amp; Wt. Per Ft.</b> | <b>Wt For 20'</b> | <b>WT Thickness Of Web in Inches</b> | <b>WT Width Of Flange in Inches</b> |
|---|-------------------|--------------------------------------|-------------------------------------|
| 3" X 5.7 lbs.                               | 114               | 0.17                                 | 2.33                                |
| 3" X 7.5 lbs.                               | 150               | 0.349                                | 2.509                               |
| 4" X 7.7 lbs.                               | 154               | 0.19                                 | 2.66                                |
| 4" X 9.5 lbs.                               | 190               | 0.326                                | 2.796                               |
| 5" X 10.0 lbs.                              | 200               | 0.21                                 | 3                                   |
| 5" X 14.75 lbs.                             | 295               | 0.494                                | 3.284                               |
| 6" X 12.5 lbs.                              | 250               | 0.23                                 | 3.33                                |
| 6" X 17.25 lbs.                             | 345               | 0.465                                | 3.565                               |
| 7" X 15.3 lbs.                              | 306               | 0.25                                 | 3.66                                |
| 7" X 20.0 lbs.                              | 400               | 0.45                                 | 3.86                                |
| 8" X 18.4 lbs.                              | 368               | 0.27                                 | 4                                   |
| 8" X 23.0 lbs.                              | 460               | 0.441                                | 4.171                               |
| 10" X 25.4 lbs.                             | 508               | 0.31                                 | 4.66                                |
| 10" X 35.0 lbs.                             | 700               | 0.594                                | 4.944                               |
| 12" X 31.8 lbs.                             | 636               | 0.35                                 | 5                                   |
| 12" X 35.0 lbs.                             | 700               | 0.428                                | 5.078                               |
| 12" X 40.8 lbs.                             | 816               | 0.46                                 | 5.25                                |
| 12" X 50.0 lbs.                             | 1000              | 0.687                                | 5.477                               |
| 15" X 42.9 lbs.                             | 858               | 0.41                                 | 5.5                                 |
| 15" X 50.0 lbs.                             | 1000              | 0.55                                 | 5.64                                |
| 18" X 54.7 lbs.                             | 1094              | 0.46                                 | 6                                   |
| 18" X 70.0 lbs.                             | 1400              | 0.711                                | 6.251                               |



**ADDISON STL**

| <u>D Depth of Channel &amp; Wt. Per Ft.</u> | <u>Wt For 20'</u> | <u>WT Thickness Of Web in Inches</u> | <u>WT Width Of Flange in Inches</u> |
|---|-------------------|--------------------------------------|-------------------------------------|
| 20" X 66.0 lbs.                             | 1320              | 0.505                                | 6.255                               |
| 24" X 80.0 lbs.                             | 1600              | 0.5                                  | 7                                   |
| 24" X 100.0 lbs.                            | 2000              | 0.747                                | 7.247                               |
| 24" X 106.0 lbs.                            | 2120              | 0.625                                | 7.875                               |